

# RE50大电流双极跷板开关 22(14)A 250Vac



- ▶ 额定电流可达22A
- ▶ 防水防尘设计，  
适合在恶劣环境下使用
- ▶ 外表协调美观
- ▶ 双极



22(14)A 250Vac 5E4  
25T105/55 IP55



22A 125/250Vac  
2HP 250Vac/125Vac  
T100

**R E 50 C ---**

系列 类别 功能 端子 特征序号：壳体、按钮、印字、颜色等

| 功 能       |                                | 端 子                  | 壳 体   | 按 钮                            |                                |                                |           |    |  |          |      |      |         |      |  |  |
|-----------|--------------------------------|----------------------|---|--------------------------------|--------------------------------|--------------------------------|-----------|----|--|----------|------|------|---------|------|--|--|
|           |                                | <b>C 6.3X0.8</b><br> | 面板开孔<br><br>外端<br><br><table border="1"> <tr> <td>面板厚度</td> <td>X<sup>+0.1</sup><sub>0</sub></td> <td>Y<sup>+0.1</sup><sub>0</sub></td> </tr> <tr> <td>0.75~1.25</td> <td>30</td> <td></td> </tr> <tr> <td>1.25~2.0</td> <td>30.3</td> <td>22.1</td> </tr> <tr> <td>2.0~4.0</td> <td>30.6</td> <td></td> </tr> </table> | 面板厚度                           | X <sup>+0.1</sup> <sub>0</sub> | Y <sup>+0.1</sup> <sub>0</sub> | 0.75~1.25 | 30 |  | 1.25~2.0 | 30.3 | 22.1 | 2.0~4.0 | 30.6 |  |  |
| 面板厚度      | X <sup>+0.1</sup> <sub>0</sub> |                      |   | Y <sup>+0.1</sup> <sub>0</sub> |                                |                                |           |    |  |          |      |      |         |      |  |  |
| 0.75~1.25 | 30                             |                      |   |                                |                                |                                |           |    |  |          |      |      |         |      |  |  |
| 1.25~2.0  | 30.3                           | 22.1                 |   |                                |                                |                                |           |    |  |          |      |      |         |      |  |  |
| 2.0~4.0   | 30.6                           |                      |   |                                |                                |                                |           |    |  |          |      |      |         |      |  |  |
| RE50      | ON-OFF                         |                      |   |                                |                                |                                |           |    |  |          |      |      |         |      |  |  |
| RE60      | ON-ON                          |                      |   |                                |                                |                                |           |    |  |          |      |      |         |      |  |  |
| 外形尺寸 (mm) |                                |                      |   |                                |                                |                                |           |    |  |          |      |      |         |      |  |  |
|           |                                |                      |   |                                |                                |                                |           |    |  |          |      |      |         |      |  |  |