

RF00跷板开关-单极 16(6)A 250Vac



- ▶ 标准型跷板开关
- ▶ 可带灯
- ▶ 通断电流可选
- ▶ 多种外观形式
- ▶ 多种安装孔尺寸
- ▶ 外表协调美观
- ▶ 单极



16(6)A 250Vac 1E4
10(10)A 250Vac 5E4
25T125/55



16A 125/250Vac
125Vac 3/4HP
250Vac 3/2HPT100

R F 03 C - - -

系列 类别 功能 端子 特征序号: 壳体、按钮、印字、颜色、电压等

功 能		端 子	壳 体	按 钮																				
		C 6.3X0.8	面板开孔 <table border="1"> <tr> <td>面板厚度</td> <td>X^{+0.1}₀</td> <td>Y^{+0.1}₀</td> <td></td> <td></td> </tr> <tr> <td>0.75-1.25</td> <td>28.6</td> <td></td> <td></td> <td></td> </tr> <tr> <td>1.25-2.0</td> <td>28.8</td> <td>13.8</td> <td>12.1</td> <td>13.4</td> </tr> <tr> <td>2.0-3.0</td> <td>29.2</td> <td></td> <td></td> <td></td> </tr> </table>	面板厚度	X ^{+0.1} ₀	Y ^{+0.1} ₀			0.75-1.25	28.6				1.25-2.0	28.8	13.8	12.1	13.4	2.0-3.0	29.2				标准型 带灯标准型
面板厚度	X ^{+0.1} ₀	Y ^{+0.1} ₀																						
0.75-1.25	28.6																							
1.25-2.0	28.8	13.8	12.1	13.4																				
2.0-3.0	29.2																							
RF00 ON-OFF																								
RF01 (ON) -OFF (瞬通)		D 6.3X0.8																						
RF02 ON- (OFF) (瞬断)																								
RF03 ON-OFF (带灯)		H 4.7X0.8	外端 	V型 带灯V型 																				
RF08 ON-OFF (灯常亮)		T 焊接																						
RF10 ON-ON																								
RF11 (ON) -ON (一侧复位)																								
RF20 ON-OFF-ON																								
RF21 (ON) -OFF-ON (一侧复位)																								
RF22 (ON) -OFF- (ON) (两侧复位)																								

注意: 五金面板由开关装入方向冲孔

印 字	选 项	外形尺寸 (mm)
1 2 3 4 5 6	印刷图形: 选择左侧图案或提供图案定做。 颜色: 无灯开关壳体和按钮颜色可选黑、白、灰, 带灯开关按钮可选透明红、绿、橙、无色。 特殊要求可定做。 灯电压: 带灯开关需明确光源种类(氖灯、LED)和灯的使用电压, 标准型为: 氖灯 220Vac	