

# SA00跷板开关-双联体单元 16A 250Vac



- ▶ 小型双联单元跷板开关
- ▶ 额定电流可达16A
- ▶ 适用于快接、焊接和印刷电路板端子
- ▶ 带灯和无灯形式
- ▶ 外表协调美观



16A 250Vac 1E4  
8(8)A 250Vac 5E4  
25T125/55



16A 125/250Vac  
125Vac 3/4HP  
250Vac 3/2HPT100

**S A 03 H --- /SA03H---**

系列 类别 功能 端子 特征序号: 壳体、按钮、印字、颜色、电压等

功 能		端 子	壳 体	按 钮												
		<b>H</b> 4.7X0.8 	面板开孔 	标准型 												
SA00/ SA00	ON-OFF ON-OFF 	<b>T</b> 焊接 	<table border="1"> <tr> <th>面板厚度</th> <th>X<sup>+0.1</sup><sub>0</sub></th> <th>Y<sup>+0.1</sup><sub>0</sub></th> </tr> <tr> <td>0.75~1.25</td> <td>19.0</td> <td>22.0</td> </tr> <tr> <td>1.25~2.0</td> <td>19.3</td> <td>22.0</td> </tr> <tr> <td>2.0~3.0</td> <td>19.6</td> <td>22.0</td> </tr> </table> 注意: 五金面板由开关装入方向冲孔	面板厚度	X <sup>+0.1</sup> <sub>0</sub>	Y <sup>+0.1</sup> <sub>0</sub>	0.75~1.25	19.0	22.0	1.25~2.0	19.3	22.0	2.0~3.0	19.6	22.0	带灯标准型 
面板厚度	X <sup>+0.1</sup> <sub>0</sub>	Y <sup>+0.1</sup> <sub>0</sub>														
0.75~1.25	19.0	22.0														
1.25~2.0	19.3	22.0														
2.0~3.0	19.6	22.0														
SA01/ SA01	(ON) -OFF (ON) -OFF (瞬通) 	<b>X</b> 	PCB 板孔位图 													
SA03/ SA03	ON-OFF ON-OFF (带灯) 															
SA10/ SA10	ON-ON ON-ON 															
SA20/ SA20	ON-OFF-ON ON-OFF-ON 															
SA10/ SA20	ON-ON ON-OFF-ON 															

选 项
<b>印刷图形:</b> 选择SA00图案或提供图案定做。
<b>颜色:</b> 无灯开关壳体 and 按钮颜色可选黑、白、灰, 带灯开关按钮可选透明红、绿、橙、无色。特殊要求可定做。
<b>灯电压:</b> 带灯开关需明确光源种类(氖灯、LED)和灯的使用电压, 标准型为: 氖灯 220Vac

外形尺寸 (mm)